



# RAVENOL SCOOTER 4-Takt Teilsynth.



1L | 1152155-001  
4L | 1152155-004  
10L | 1152155-010  
20L | 1152155-020  
20L | 1152155-B20  
60L | 1152155-060  
60L | 1152155-D60  
208L | 1152155-208  
1000L | 1152155-700

**Kategorie:** 4 stroke engine oil

**Artikelnummer:** 1152155

**Specification:** API SL, SAE 10W-40

**Oil type:** Semi-synthetic

**Recommendation:** Aprilia, Arctic Cat, Argo, Bombardier, Dinli, Honda, Kawasaki, Peugeot, Piaggio, Polaris, Suzuki, Yamaha

**Application:** Motorcycle

**RAVENOL SCOOTER 4-Takt Teilsynth.** is a semi-synthetic high quality green dyed motor oil for small 4-stroke engines. Special ingredients provide a clean motor and clean intake and exhaust systems. This provides impeccable lubrication and wear protection.

**RAVENOL SCOOTER 4-Takt Teilsynth.** enables an energy-saving operation of motors because of its additives and the selection of base oils and viscosity characteristics.

Special ingredients in **RAVENOL SCOOTER 4-Takt Teilsynth.** provide for a clean motor and clean intake and exhaust systems.

**RAVENOL SCOOTER 4-Takt Teilsynth.** is the product for an ideal service life of the engine.

## Application Note

**RAVENOL SCOOTER 4-Takt Teilsynth.** is for use in small 4-stroke engines.

## Characteristics

- High wear protection
- Fuel saving due to smooth-running properties
- Excellent detergent and dispersant properties
- Prevention of black sludge formation
- Long service life due to outstanding oxidation stability
- Excellent cold start performance
- Very good viscosity-temperature characteristics
- Low tendency to evaporation

## Technical Product Data

| PROPERTY                                    | UNIT               | DATA   | AUDIT           |
|---|--------------------|--------|-----------------|
| Density at 20 °C                            | kg/m <sup>3</sup>  | 862,0  | EN ISO 12185    |
| Colour                                      |                    | grün   | VISUELL         |
| Viscosity at 100 °C                         | mm <sup>2</sup> /s | 14,4   | DIN 51562-1     |
| Viscosity at 40 °C                          | mm <sup>2</sup> /s | 97,6   | DIN 51562-1     |
| Viscosity Index VI                          |                    | 153    | DIN ISO 2909    |
| HTHS Viscosity at 150 °C                    | mPa*s              | 4,03   | ASTM D5481      |
| CCS Viscosity at -35 °C                     | mPa*s              | 5351   | ASTM D5293      |
| Low Temp. Pumping viscosity (MRV) at -40 °C | mPa*s              | 14.130 | ASTM D4684      |
| Pourpoint                                   | °C                 | -39    | DIN ISO 3016    |
| Noack Volatility                            | % M/M              | 10,3   | ASTM D5800      |
| Flashpoint                                  | °C                 | 229    | DIN EN ISO 2592 |
| tbn   | mg KOH/g           | 9,8    | ASTM D2896      |
| Sulphated Ash                               | %wt.               | 1,5    | DIN 51575       |

All indicated data are approximate values and are subject to the commercial fluctuations.