



RAVENOL MARINEOIL PETROL SAE 25W40 synthetic



1L | 1162115-001
4L | 1162115-004
10L | 1162115-010
20L | 1162115-020
20L | 1162115-B20
60L | 1162115-060
60L | 1162115-D60
208L | 1162115-208
1000L | 1162115-700

Kategorie: Marine engine oil

Artikelnummer: 1162115

Viscosity: 25W-40

Specification: ACEA A3/B4, API SL

Oil type: Synthetic

Recommendation: Caterpillar, Detroit Diesel, IVECO, MAN, Mercruiser, MTU, NANNI Diesel, PERKINS, SKL, STEYR, SULZER, VETUS DEUTZ, VOLVO PENTA, Yanmar

Application: Marine

RAVENOL MARINEOIL PETROL 25W-40 synthetic is an engine oil for the use in marine petrol engines.

RAVENOL MARINEOIL PETROL 25W-40 synthetic is produced with unconventional and HC basic oils, synthetic components and additives.

RAVENOL MARINEOIL PETROL 25W-40 synthetic guarantees longest oil change intervals and a high corrosion protection with a low oil and fuel consumption.

Application Note

RAVENOL MARINEOIL PETROL 25W-40 synthetic is tried and tested for aggregates specifying:

Specifications: API SL, ACEA A3/B4

Recommendations: Caterpillar, Detroit Diesel, IVECO, MAN, Mercruiser, MTU, NANNI Diesel, PERKINS, SKL, Steyr, SULZER, VETUS DEUTZ, VOLVO PENTA, Yanmar.

Characteristics

- Excellent detergent and dispersant characteristics
- Low evaporation
- High aging stability
- Protection of reflecting surface formation
- Very good cold start characteristics
- Reduces oil and fuel consumption

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	866,0	EN ISO 12185
Colour		blau	VISUELL
Viscosity at 100 °C	mm ² /s	13,8	DIN 51562-1
Viscosity at 40 °C	mm ² /s	92,4	DIN 51562-1
Viscosity Index VI		152	DIN ISO 2909
CCS Viscosity at -25 °C	mPa*s	6450	ASTM D5293
Pourpoint	°C	-36	DIN ISO 3016
Flashpoint	°C	215	DIN EN ISO 2592
tbn	mg KOH/g	11,0	ASTM D2896
Sulphated Ash	%wt.	1,3	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

27.01.2023