



# RAVENOL MARINEOIL PETROL SAE 15W-40

RAVENOL MARINEOIL PETROL SAE 15W-40

**1L | 1163200-001**  
**4L | 1163200-004**  
**10L | 1163200-010**  
**20L | 1163200-020**  
**20L | 1163200-B20**  
**60L | 1163200-060**  
**208L | 1163200-208**

**Kategorie:** Marine engine oil

**Artikelnummer:** 1163200

**Viscosity:** 15W-40

**Specification:** API SL

**Oil type:** Mineral

**Recommendation:** Kohler, Mercruiser, VOLVO PENTA AB, Yanmar

**Application:** Marine

**RAVENOL MARINEOIL PETROL SAE 15W-40** is a high additive treated HD engine oil for marine gasoline engines.

**RAVENOL MARINEOIL PETROL SAE 15W-40** is especially produced for extended oil change intervals (under consideration of the manufacturer instruction).

## Application Note

**RAVENOL MARINEOIL PETROL SAE 15W-40** is tried and tested for aggregates specifying:

Specification: API SL

Recommendations: VOLVO Penta AB, Mercruiser, Yanmar, Kohler

## Characteristics

- an extreme high pressure absorption capacity
- a very high oxidation stability
- an excellent aging resistance
- an excellent viscosity temperature behaviour
- high safety reserves also under boundary lubrication conditions
- suitability for extended oil change intervals
- suitability for complicate operating conditions

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	879,5	EN ISO 12185
Colour		blau	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	15,0	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	115,7	DIN 51562-1
Viscosity Index VI		134	DIN ISO 2909
Pourpoint	°C	-36	DIN ISO 3016
Flashpoint	°C	238	DIN EN ISO 2592
tbn	mg KOH/g	10,5	ASTM D2896

All indicated data are approximate values and are subject to the commercial fluctuations.

**Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.**

23.03.2023