



# RAVENOL Hydraulik PSF Fluid

**Kategorie:** Car hydraulic oil

**Artikelnummer:** 1181000

**Oil type:** Synthetic

**Recommendation:** Citroën/Peugeot 9735EJ für C-Crosser, Peugeot 4007, Honda PSF-S, Hyundai PSF-3, KIA PSF-III, Mazda PSF, Mitsubishi Diamond PSF-2M, Peugeot 4007, Subaru PS Fluid, Toyota PSF-EH

**Application:** Passenger car



**RAVENOL Hydraulik PSF Fluid** is a specific synthetic hydraulic fluid for power steering.

**RAVENOL Hydraulik PSF Fluid** is guaranteeing an optimized power transmission.

**RAVENOL Hydraulik PSF Fluid** is produced on the basis of high quality base oils with special additives and inhibition which guarantees a perfect function of the hydraulics.

## Application Note

**RAVENOL Hydraulik PSF Fluid** is especially developed for the use as a hydraulic fluid in power transmissions.

## Characteristics

- A very low pour point
- An excellent foam prevention, no foam formation
- A good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- A very good oxidation stability
- Excellent protection against wear and tear, corrosion and foam formation
- Fine tuned coefficient of friction
- eutral behaviour against sealing materials
- Neutral behaviour because of inhibition against non ferrous metals

1L | 1181000-001

4L | 1181000-004

10L | 1181000-010

20L | 1181000-020

20L | 1181000-B20

60L | 1181000-060

208L | 1181000-208

1000L | 1181000-700

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	847,0	EN ISO 12185
Colour		rot	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	7,2	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	34,8	DIN 51562-1
Viscosity Index VI		178	DIN ISO 2909
Brookfield Viscosity at -40 °C	mPa*s	12800	ASTM D2983
Pourpoint	°C	-48	DIN ISO 3016
Flashpoint	°C	211	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.

**Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.**

26.01.2023