



# RAVENOL CVTF NS2/J1 Fluid

**Kategorie:** Gear oil for automatic transmissions

**Artikelnummer:** 1211114

**Oil type:** Synthetic

**Recommendation:** Mitsubishi S0001401, Nissan CVT NS-2, Nissan KLE52-0002, Nissan KLE52-0004, PSA 9735EF, Suzuki CVT Fluid Green-1 99000-22B15-046

**Application:** Passenger car



**RAVENOL CVTF NS2/J1 Fluid** is a synthetic CVTF (Continuously Variable Transmission Fluid) produced on the basis of high-quality hydrocrack oils with special additives and inhibition which guarantees a perfect function of the CVT transmission.

**RAVENOL CVTF NS2/J1 Fluid** is a CVTF of the latest generation. It is especially developed for the CVT transmission of JATCO. It guarantees in any mode for maximum wear protection.

**RAVENOL CVTF NS2/J1 Fluid** is green coloured.

1L | 1211114-001

4L | 1211114-004

10L | 1211114-010

20L | 1211114-020

20L | 1211114-B20

60L | 1211114-060

60L | 1211114-D60

208L | 1211114-208

208L | 1211114-D28

## Application Note

**RAVENOL CVTF NS2/J1 Fluid** is suitable for use in CVT transmission of following vehicles with CVT-transmission: Peugeot 4007, Citroen C-Crosser, Mitsubishi Outlander, Mitsubishi Delica D5, Mitsubishi Galant Fortis, Mitsubishi RVR, Mitsubishi Lancer 1.8 CY0 2007, Nissan Murano, Nissan Teana, Nissan Maxima, Nissan Presage, Nissan X-Trail, Nissan Lafesta, Nissan Serena, Nissan Bluebird Sylphy, Nissan Dualis, Suzuki Kizachi, Suzuki SX4, Dodge Caliber, Jeep Compass, Jeep Patriot and other models with CVT-transmission JATCO JF011E (RE0F10A, F1CJA) or JF010E (RE0F09A). Maintenance-filling under normal operating conditions.

## Characteristics

- Very good lubricating ability even at low temperatures in winter
- A high, stable viscosity index
- Very good oxidation stability
- Protection against corrosion and foam formation
- Good balanced coefficient of friction
- A high thermal and oxidative stability
- An excellent cooling capacity

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	846,0	EN ISO 12185
Colour		grün	VISUELL
Pourpoint	°C	-45	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

RAVENOL special transmission fluids are special developments for special gears and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. If you are unsure about the right transmission fluid, ask your workshop or dealership for advice on the transmission type and OEM original number or ask our experts, making sure to state the VIN code (vehicle identification number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. and cause the failure of the transmission. Ravensberger Schmierstoffvertrieb GmbH is not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.