



RAVENOL ATF MM SP-III Fluid

Kategorie: Gear oil for automatic transmissions

Artikelnummer: 1212103

Oil type: Synthetic

Recommendation: ATF SP-3, ATF SP-III, Chery B110AX4004011SP10, Chery CHR2015CVT001, Chery CVT 019CHA/019CHB, Hyundai 00232-19012, Hyundai 04500-00100, Hyundai 04500-00400, Hyundai 04500-00A00, Mitsubishi 4024401, Mitsubishi 4024610, Mitsubishi ACH1ZC1X05, Mitsubishi MZ320159, Mitsubishi MZ320160, Mitsubishi MZ320162, Mitsubishi MZ320216

Application: Passenger car



RAVENOL ATF MM SP-III Fluid is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

RAVENOL ATF MM SP-III Fluid is universal ATF (Automatic Transmission Fluid) for automatic transmission of Mitsubishi, Hyundai and KIA.

RAVENOL ATF MM SP-III Fluid guarantees maximum wear protection in all operating conditions.

1L | 1212103-001

4L | 1212103-004

10L | 1212103-010

20L | 1212103-020

20L | 1212103-B20

60L | 1212103-060

60L | 1212103-D60

208L | 1212103-208

208L | 1212103-D28

1000L | 1212103-700

Application Note

RAVENOL ATF MM SP-III Fluid was developed for use in automatic transmission, especially for Mitsubishi, Hyundai and KIA.

RAVENOL ATF MM SP-III Fluid can replace SP und SP-II Fluids.

It is advisable to flush with **RAVENOL ATF MM SP-III Fluid** before filling with **RAVENOL ATF MM SP-III Fluid**.

Characteristics

- Very good lubricating properties also at low temperatures in winter
- High, stable viscosity index
- Very low pour point
- Excellent oxidation stability
- Protection against wear, corrosion and foaming
- Good concerted friction characteristic
- Neutral behavior towards sealing materials
- Neutral behavior by inhibition to non-ferrous metals

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	847,0	EN ISO 12185
Colour		rot	VISUELL
Pourpoint	°C	-48	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

RAVENOL special transmission fluids are special developments for special gears and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. If you are unsure about the right transmission fluid, ask your workshop or dealership for advice on the transmission type and OEM original number or ask our experts, making sure to state the VIN code (vehicle identification number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. and cause the failure of the transmission. Ravensberger Schmierstoffvertrieb GmbH is not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.