



# RAVENOL Hydraulikoel HLP-D 68

**Kategorie:** Other hydraulic oil

**Artikelnummer:** 1323306

**Viscosity:** 68

**Specification:** DIN 51524-3

**Oil type:** Mineral

**Recommendation:** Daimler DBL 6721, MAN N 698, Parker Denison HF-0

**Application:** Industry

RAVENOL Hydraulikoel HLP-D 68

is detergent hydraulic oil with good net and cleaning effect.

RAVENOL Hydraulikoel HLP-D 68

is designed with selected base oils with additives to prevent corrosion, wear and friction.

RAVENOL Hydraulikoel HLP-D 68

also contains detergent and dispersing agents, which always provide for a clean hydraulic system. These additives dissolve contaminants, hold them in suspension and enabling the cleaning of contaminated hydraulic systems. The functional elements of a hydraulic system thereby remain free of deposits and bonds. This will emulsified penetrating water and ensure trouble-free operation of the hydraulic system.

## Application Note

### RAVENOL Hydraulikoel HLP-D 6

is for use in agriculture hydraulic systems, construction machinery, cement factories, foundries, and electro-plate clutches. It can also be used as functional test oil, inlet oil for aggregates and machinery, textile machinery and machine tools.

60L | 1323306-060

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	9,4	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	69,2	DIN 51562-1
Viscosity Index VI		113	DIN ISO 2909
Density at 20 °C	kg/m <sup>3</sup>	869,0	EN ISO 12185
Flashpoint	°C	234	DIN EN ISO 2592
Pourpoint	°C	-36	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

**Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.**

02.12.2022