



RAVENOL ODL 32 Druckluftoel

Kategorie: Hydraulic oil

Artikelnummer: 1323404

Viscosity: 32

Oil type: Mineral

Recommendation: Atlas Copco Kompressor, Black & Decker, Bosch, Cress, DeWalt, Festo, Hilti, Hitachi, Makita, Ryobi, Seno, Sumake

Application: Industry



RAVENOL ODL 32 Druckluftoel is a special-compressed-air-oil for pneumatic tools of all systems.

RAVENOL ODL 32 Druckluftoel bonds condensed water, has an excellent corrosion protection, wear protection and an extraordinary pressure absorption capacity, a good adhesive power and high aging resistance. Easily conveying- and spray ability, economy consumption. No deposits caused by cleaning effects. Full power of impact.

Application Note

RAVENOL ODL 32 Druckluftoel is especially suitable for pneumatic tools with sound-absorbing-case, for lubrication of rock drills, road breaker, chipping hammer and spade hammer, ram machines and other pneumatic aggregates. Application by pre-switch-lubricator according to working instructions or usable directly in the air pipe.

Please follow the manufacturer's instructions.

Characteristics

- a high performance level
- a very good viscosity temperature behaviour
- a good adherence
- a high aging resistance
- a reliable wear protection
- an excellent corrosion protection
- neutrality of sealing materials

5L | 1323404-005

10L | 1323404-010

20L | 1323404-020

20L | 1323404-B20

60L | 1323404-060

208L | 1323404-208

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	848,0	EN ISO 12185
Colour		hellgelb	VISUELL
Viscosity at 100 °C	mm ² /s	5,8	DIN 51562-1
Viscosity at 40 °C	mm ² /s	32,1	DIN 51562-1
Viscosity Index VI		123	DIN ISO 2909
Pourpoint	°C	-30	DIN ISO 3016
Flashpoint	°C	224	DIN EN ISO 2592
FZG-Test A/8.3/90 Damage loading step	%wt.	12	DIN 51354/2

All indicated data are approximate values and are subject to the commercial fluctuations.