



RAVENOL Turbo Oil T32



20L | 1331114-020
60L | 1331114-060
208L | 1331114-208

Kategorie: Industrial oil

Artikelnummer: 1331114

Viscosity: 32

Specification: DIN 51515-1 L-TD, DIN 51515-2 L-TG

Oil type: Mineral

Approvals: Siemens TLV 901304, Siemens TLV 901305

Recommendation: Alstom HTGD 90117 V0001 S, British Standard BS 489, Brown Boveri HTGD 90117, CEGB Standard 207001, General Electric GEK 32568 A, General Electric GEK 32568 C, MIL-L-17672 D, U.S. Steel 120, Westinghouse Electric Corp. Turbine Oil Spec.

Application: Industry

RAVENOL Turbo Oil T32

is a high quality lubricating oil for gas and steam turbines as well as for turbo compressors with and without gears, which meets the requirements of DIN 51515-2.

RAVENOL Turbo Oil T32

is based on high quality base oils with additives to improve the corrosion protection and resistance to aging.

RAVENOL Turbo Oil T32

is an all-purpose oil for turbines from specially selected base oils with the addition of special refined additives.

Application Note

RAVENOL Turbo Oil T3

is used in stationary gas turbines, steam turbines and also in electrical or in driven by steam machines, such as generators, compressors, pumps and gearboxes.

RAVENOL Turbo Oil T3

is also for use in lubrication of hydraulic systems, compressors, gear transmissions and bearings.

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	849,0	EN ISO 12185
Colour		L1.5	DIN ISO 2049
Viscosity at 100 °C	mm ² /s	5,8	DIN 51562-1
Viscosity at 40 °C	mm ² /s	32,1	DIN 51562-1
Viscosity Index VI		122	DIN ISO 2909
Pourpoint	°C		DIN ISO 3016
Flashpoint	°C	232	DIN EN ISO 2592
Water Separability	s	35	DIN 51589-1
Foam Volume at 25 °C	ml	60	ISO 6247
Time to collapse of the foam at 25 °C	s	245	ISO 6247
Residual foam after 600 s at 25 °C	ml	0	ISO 6247
Copper strip corrosion		pass	DIN EN ISO 2160
FZG Pass Load Stage		10	DIN ISO 14635-1
Water content	%		DIN 51777-1
NZ Neutralisation number	mg KOH/g	0,06	DIN 51558-1
Air release at 50 °C, max.	min	3	DIN ISO 9120
Purity grade		19/16/13	ISO 4406

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

04.12.2022