



20L | 1332106-020  
20L | 1332106-B20  
208L | 1332106-208  
1000L | 1332106-700

# RAVENOL Getriebeoil CLP 68

**Kategorie:** Industrial oil

**Artikelnummer:** 1332106

**Viscosity:** 68

**Specification:** DIN 51517-3

**Oil type:** Mineral

**Recommendation:** AGMA 9005-D94, Cincinnati Milacron, Clean Panel Coker, FZG 12, S-200 Oxidation Tubes, US Steel 224

**Application:** Industry

**RAVENOL Getriebeoil CLP 68** is a high quality, mineral-based gear oil formulated with lead-free high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity.

**RAVENOL Getriebeoil CLP 68** has a low pour point and therefore a very good cold behaviour.

## Application Note

**RAVENOL Getriebeoil CLP 68** can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

## Characteristics

- A very good, stable high-pressure impact capacity
- Resistant characteristics at high temperatures
- A good rust and corrosion impeding effect
- Excellent wear protection
- Very good anti-foaming characteristics
- A low pour point
- Very good cold behaviour

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	879,0	EN ISO 12185
Colour		braun	VISUELL
Viscosity at 100 °C	mm <sup>2</sup> /s	8,6	DIN 51562-1
Viscosity at 40 °C	mm <sup>2</sup> /s	67,0	DIN 51562-1
Viscosity Index VI		100	DIN ISO 2909
Pourpoint	°C	-24	DIN ISO 3016
Flashpoint	°C	220	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.

**Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.**

27.01.2023