



20L | 1332108-020
60L | 1332108-060
208L | 1332108-208
1000L | 1332108-700

RAVENOL Getriebeoil CLP 150

Kategorie: Industrial oil

Artikelnummer: 1332108

Viscosity: 150

Specification: DIN 51517-3

Oil type: Mineral

Recommendation: AGMA 9005-D94, Cincinnati Milacron, Clean Panel Coker, S-200 Oxidation Tubes, US Steel 224

Application: Industry

RAVENOL Getriebeoil CLP 150 is a high quality, mineral-based gear oil formulated with lead-free high-pressure additives (EP additives). Its special active substance combination provides a good, stable high-pressure impact load capacity.

RAVENOL Getriebeoil CLP 150 has a low pour point and therefore a very good cold behaviour.

Application Note

RAVENOL Getriebeoil CLP 150 can be used as a lubricant in nearly all industrial gear drives due to its good stress and/or impact characteristics.

Characteristics

- A very good, stable high-pressure impact capacity.
- Resistant characteristics at high temperatures
- A good rust and corrosion impeding effect
- Excellent wear protection
- Very good anti-foaming characteristics
- A low pour point
- Very good cold behaviour

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	884,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	14,8	DIN 51562-1
Viscosity at 40 °C	mm ² /s	152,9	DIN 51562-1
Viscosity Index VI		96	DIN ISO 2909
Pourpoint	°C	-30	DIN ISO 3016
Flashpoint	°C	256	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

02.12.2022