



RAVENOL Getriebeoel CLP 680



20L | 1332112-020
20L | 1332112-B20
208L | 1332112-208
1000L | 1332112-700

Kategorie: Industrial oil

Artikelnummer: 1332112

Viscosity: 680

Specification: DIN 51517-3

Oil type: Mineral

Recommendation: AGMA 9005-D94, Cincinnati Milacron, Clean Panel Coker, S-200 Oxidation Tubes, US Steel 224

Application: Industry

RAVENOL Getriebeoel CLP 680 is a high quality transmission fluid on a mineral oil basis, formulated with unleaded high pressure additives (EP additives). A very good, stable high pressure absorption capacity for impact loads is achieved due to its special combination of ingredients.

RAVENOL Getriebeoel CLP 680 has a low pour point and therefore, an extremely good low-temperature performance.

Application Note

RAVENOL Getriebeoel CLP 680 can be used as a lubricant in almost all industrial gears under heavy load and / or shock load due to its excellent properties.

Characteristics

- Excellent, stable high pressure absorption capacity for impact loads
- Stable properties in increased temperatures
- A good rust-inhibiting and anticorrosive effect
- Excellent wear protection
- Very good effect against foaming
- A low pour point
- Excellent low-temperature performance

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	903,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	37,4	DIN 51562-1
Viscosity at 40 °C	mm ² /s	666,2	DIN 51562-1
Viscosity Index VI		91	DIN ISO 2909
Pourpoint	°C	-12	DIN ISO 3016
Flashpoint	°C	312	DIN EN ISO 2592

All indicated data are approximate values and are subject to the commercial fluctuations.

05.10.2022