



RAVENOL Marinefett

Kategorie: Grease

Artikelnummer: 1340128

Specification: DIN 51502: KP2K-30, ISO 6743-9: ISO-L-XCCFB2

Application: Marine



0.4L | 1340128-400

1L | 1340128-001

15L | 1340128-015

RAVENOL Marinefett is a yellow-green, fluorescent, sea-water resistant lubrication grease with long-term adhesion properties. It is based on a special, calcium soap and a high-viscous synthetic base oil, as well as specifically selected active ingredients to protect against oxidation, rust and corrosion.

RAVENOL Marinefett is a high-pressure grease with exceptionally good adhesion and threading properties. Bearing wear is effectively reduced even under extreme loads.

RAVENOL Marinefett is extremely water-resistant and particularly resistant against washing out from bearings, sliding points and metal surfaces.

RAVENOL Marinefett provides protections against corrosion for ship parts that are exposed to seawater.

RAVENOL Marinefett is preferred in the marine sector. However, it can also be used wherever a calcium-soaped grease is required - in industry, for motor vehicles, by do-it-yourselfers and in the home.

Application Note

RAVENOL Marinefett is used as boat grease for external parts of ships that are exposed to saline air humidity and direct contact with seawater and require a high degree of rust and corrosion protection. (e.g. periscopes and turret hatch closures of submarines).

RAVENOL Marinefett can be used for external lubrication in industry and farming, e.g. machines, metal parts, joints, wire ropes that are exposed to damp air, wet mine conditions or usual environmental influences.

RAVENOL Marinefett can be used to lubricate sliding and rolling bearings, guides, control levers and water pumps that are exposed to thermal and mechanical normal loaded. Also for greasing and protecting vehicle parts at risk of rusting (engine compartment, doors, car boot, welding seams, cavities). Any rust should be removed before applying the grease a.

RAVENOL Marinefett can be used over a broad temperature range and provides extremely good protection against corrosion due to its good adhesion properties.

Characteristics

- Seawater resistant
- Excellent adhesion properties
- Universal use

- Extremely shear stable
- Exceedingly excellent wear protection
- Very good mechanical and chemical stability
- Very good corrosion protection
- Very good resistance to ageing
- Good pumpability, also at low temperature

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		gelblich-grün	VISUELL
Thickener		Calcium-Komplexseifen	DIN 51757
NLGI-Class		2	DIN 51818
Product Classification		KP2K-30	DIN 51502
Working Temperature	°C	-30 / +120	DIN 51825
Short term temperature up to	°C	130	DIN 51757
Worked Penetration at 60 Strokes	mm/10/25°C	265-295	ISO 2137
Corrosion (SKF Emscor dist. Water)	Korr. Grad	0	DIN 51802
Dropping Point	°C	>150	DIN ISO 2176
Copper Corrosion (24h/120 °C)		1	DIN 51811
Water Resistance (3h/90 °C)	°C	0-90	DIN 51807-1
VKA Pressure Carrying Capacity	N	2600 - 2800	DIN 51350-4
Kinematic Viscosity (Base Oil) at 40 °C	mm ² /s	900	DIN 51562-1

All indicated data are approximate values and are subject to the commercial fluctuations.

Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.

06.02.2023