



# RAVENOL HJC COLD CLIMATE -60°C Protect FL22

**Kategorie:** Radiator antifreeze

**Artikelnummer:** 1410143

**Recommendation:** 08CLAG010S0 Honda E Coolant, Ford VC-10-A2, Hyundai 00232-19010, Hyundai 07100-00200, Hyundai 07100-00400, Hyundai Long Life Coolant, Mazda 000077508E20, Mazda C100CL005A4X, Mazda C122CL005A4X, Mazda FL22 Coolant, Nissan Anti-freeze Coolant (L250), Nissan KE90299934, Nissan KE90299944, Subaru Coolant 16218, Suzuki Longlife Coolant

**Application:** Passenger car

**RAVENOL HJC COLD CLIMATE -60°C** is a ready to use, prediluted with water, ethylene-glycol based and time-tested coolant without amines and silicates. This product is formulated based on a proven inhibitor development as an extended life radiator antifreeze. The product is suitable for regions with cold climate.

The quality of an antifreeze is no longer just determined by the antifreeze effect (which automatically exists in an ethylene-glycol based product), but by the rust protection. That is why automakers subject antifreeze to lengthy corrosion and cavitation tests.

**RAVENOL HJC COLD CLIMATE -60°C** protects the cooling system from rust, frost, and in summer, from overheating.

## Application Note

**RAVENOL HJC COLD CLIMATE -60°C** is a prediluted coolant with frost and rust protection for year-round use in automotive engines for regions with cold climate.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

**Instructions:** Add **RAVENOL HJC COLD CLIMATE -60°C** to radiator to fill line.

**RAVENOL HJC COLD CLIMATE -60°C** can also be used according to the mixing table. Mix **RAVENOL HJC COLD CLIMATE -60°C** with distilled water (per mixing chart) and add. Allow engine and heater to warm up, add coolant to fill level.

## Characteristics

- Excellent for light metal engines
- Good reserve alkalinity
- High-quality corrosion additives for optimal corrosion protection
- Elastomer compatible with elastomers used in automotive radiators



1.5L | 1410143-150  
5L | 1410143-005  
10L | 1410143-010  
20L | 1410143-020  
60L | 1410143-060  
208L | 1410143-208

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	1110,0	EN ISO 12185
Colour		grün	VISUELL
pH - value		8,0	ASTM D1287
Freezing point	°C	-60	ASTM D1177

All indicated data are approximate values and are subject to the commercial fluctuations.

**Alle angegebenen Daten sind ca. Werte und unterliegen handelsüblichen Schwankungen.**

27.01.2023