



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

* 1.1. Product identifier

Trade name/designation:

RAVENOL Türschloß-Enteiser

Article No.:

1430203

UFI:

CUKG-GSRY-S97M-J3FN

* 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Enteiser, Frostschutz, Automobil-Industrie

* 1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Ravensberger Schmierstoffvertrieb GmbH

Produktsicherheit
Jöllenbecker Str. 2
33824 Werther
Germany

Telephone: +49 5203 9719 0

Telefax: +49 5203 9719 40

E-mail: kontakt@ravenol.de

Website: www.ravenol.de

E-mail (competent person): sdb@ravenol.de

* 1.4. Emergency telephone number

24 hr. emergency phone number, 24h: +49 700 24 112 112 (Contract ID: RAV) / +1 872 5888271
(Contract ID: RAV)

SECTION 2: Hazards identification

* 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 3</i>)	H226: Flammable liquid and vapour.	On basis of test data.
STOT-repeated exposure (<i>STOT RE 2</i>)	H373: May cause damage to organs through prolonged or repeated exposure.	Calculation method.

* 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS08
Health hazard

Signal word: Warning



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

Hazard components for labelling:

ethanol; 1,2-Ethanediol

Hazard statements for physical hazards

H226 Flammable liquid and vapour.

Hazard statements for health hazards

H373 May cause damage to organs through prolonged or repeated exposure.

Supplemental hazard information: none**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours and spray.

Precautionary statements Response

P314 Get medical advice/attention if you feel unwell.

Precautionary statements Storage

P403 + P235 Store in a well-ventilated place. Keep cool.

Precautionary statements Disposal

P501 Dispose of contents/container to an appropriate recycling or disposal facility.

* **2.3. Other hazards****Other adverse effects:**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients* **3.2. Mixtures****Additional information:**

Regulation (EC) No. 648/2004 [Detergents regulation]: Contains: Preservative (bronopol), Fragrances and dyes.

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 64-17-5 EC No.: 200-578-6 REACH No.: 01-2119457610-43	ethanol Eye Irrit. 2 (H319), Flam. Liq. 2 (H225) Danger Specific concentration limit (SCL) Eye Irrit. 2; H319: C ≥ 50%	40 - < 50 weight-%
CAS No.: 107-21-1 EC No.: 203-473-3 REACH No.: 01-2119456816-28-XXXX	1,2-Ethanediol Acute Tox. 4 (H302), STOT RE 2 (H373) Warning	10 - < 15 weight-%
CAS No.: 78-93-3 EC No.: 201-159-0 Index No.: 606-002-00-3 REACH No.: 01-2119457290-43	butanone Eye Irrit. 2 (H319), Flam. Liq. 2 (H225), STOT SE 3 (H336) Danger EUH066	0 - < 1 weight-%
CAS No.: 5392-40-5 EC No.: 226-394-6	Citral; 3,7-Dimethyl-2,6-octadienal Eye Irrit. 2 (H319), Skin Irrit. 2 (H315), Skin Sens. 1 (H317) Warning	0 - < 0.1 weight-%
CAS No.: 138-86-3 EC No.: 205-341-0 Index No.: 601-029-00-7 REACH No.: 01-2120766421-57	dipentene Aquatic Acute 1 (H400), Aquatic Chronic 1 (H410), Flam. Liq. 3 (H226), Skin Irrit. 2 (H315), Skin Sens. 1 (H317) Warning	0 - < 0.1 weight-%



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 52-51-7 EC No.: 200-143-0 Index No.: 603-085-00-8	bronopol Acute Tox. 4 (H312, H302), Aquatic Acute 1 (H400), Eye Dam. 1 (H318), STOT SE 3 (H335), Skin Irrit. 2 (H315) Danger M-factor (acute): 10	0 - < 0.1 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended.

Following inhalation:

Remove casualty to fresh air and keep warm and at rest. When in doubt or if symptoms are observed, get medical advice. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap.
In case of skin irritation, consult a physician.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion:

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

* 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/ delayed effects: In rare cases the product can cause temporary erythema of the skin. Ingestion causes nausea, weakness and central nervous system effects.

4.3. Indication of any immediate medical attention and special treatment needed

When in doubt or if symptoms are observed, get medical advice. Treat symptomatically.

SECTION 5: Firefighting measures

* 5.1. Extinguishing media

Suitable extinguishing media:

In case of fire, use sand, extinguishing powder or alcohol resistant foam.

Unsuitable extinguishing media:

Full water jet

* 5.2. Special hazards arising from the substance or mixture

Flammable liquid and vapour. Vapours can form explosive mixtures with air. Remove persons to safety. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Reignition possible over considerable distance. Hazardous decomposition products: Carbon dioxide (CO₂), Carbon monoxide (CO)

Hazardous combustion products:

In case of fire: Gases/vapours, toxic

* 5.3. Advice for firefighters

Wear personal protection equipment (refer to section 8). In case of fire: Wear self-contained breathing apparatus.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

SECTION 6: Accidental release measures

* 6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Avoid contact with skin, eyes and clothes. Do not breathe gas/vapour.

Protective equipment:

Personal protection equipment: see section 8

Emergency procedures:

Remove all sources of ignition. Remove persons to safety. Provide adequate ventilation.

6.1.2. For emergency responders

Personal protection equipment:

Use appropriate respiratory protection.

* 6.2. Environmental precautions

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

* 6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Ventilate affected area.

For cleaning up:

Take up mechanically. Clear contaminated areas thoroughly.

Other information:

Ventilate affected area. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

SECTION 7: Handling and storage

SECTION 8: Exposure controls/personal protection

SECTION 13: Disposal considerations

6.5. Additional information

Special danger of slipping by leaking/spilling product. Use appropriate container to avoid environmental contamination.

SECTION 7: Handling and storage

* 7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Keep out of reach of children. Wash hands thoroughly after handling. Wear personal protection equipment (refer to section 8). Avoid contact with skin, eyes and clothes.

Do not breathe vapour/aerosol. After use replace the closing cap immediately.

Fire prevent measures:

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge.

In use may form flammable/explosive vapour-air mixture. Heating causes rise in pressure with risk of bursting.

Measures to prevent aerosol and dust generation:

Ensure adequate ventilation of the storage area.

Environmental precautions:

No special measures are necessary.

Advices on general occupational hygiene

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

Wash hands before breaks and after work.

* 7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed. Protect from direct sunlight.



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

Ensure adequate ventilation of the storage area. Vapours are heavier than air, spread along floors and form explosive mixtures with air.

Requirements for storage rooms and vessels:

Keep only in original container.

Hints on storage assembly:

Do not store together with: Gas, Oxidizing agent, Self-heating substances and mixtures.

Storage class (TRGS 510, Germany): 3 - Flammable liquids

Further information on storage conditions:

Recommended storage temperature: 5 -25 °C

Protect against: UV-radiation/sunlight, Heat

7.3. Specific end use(s)**Recommendation:**

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****8.1.1. Occupational exposure limit values**

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
CH from 1 Jan 2022	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 500 ppm (960 mg/m ³) ② 1,000 ppm (1,920 mg/m ³) ⑤ SSC; Tox: Formal; Messmeth: INRS NIOSH
CZ from 1 Mar 2020	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 522 ppm (1,000 mg/m ³) ② 1,566 ppm (3,000 mg/m ³)
PL	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,900 mg/m ³
NO	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 500 ppm (950 mg/m ³)
IE from 5 Dec 2011	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	② 1,000 ppm
MY from 1 Jan 2000	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,880 mg/m ³)
HTP (FI)	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,900 mg/m ³) ② 1,300 ppm (2,500 mg/m ³)
LT	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 500 ppm (1,000 mg/m ³) ② 1,000 ppm (1,900 mg/m ³)
SE from 22 Aug 2019	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 500 ppm (1,000 mg/m ³) ③ 1,000 ppm (1,900 mg/m ³)
NPEL (SK) from 23 Nov 2011	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 500 ppm (960 mg/m ³) ② 1,000 ppm (1,920 mg/m ³)
DK	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,900 mg/m ³) ② 2,000 ppm (3,800 mg/m ³)
NL from 1 Jan 2023	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 137 ppm (260 mg/m ³) ② 1,000 ppm (1,900 mg/m ³) ⑤ (Kankerverwekkend, kan door de huid in het lichaam worden opgenomen) H



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,900 mg/m ³)
MAK (AT)	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	② 2,000 ppm (3,800 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
BG	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 mg/m ³
HR	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,900 mg/m ³)
BE	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,907 mg/m ³)
RO	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,900 mg/m ³) ② 5,000 ppm (9,500 mg/m ³)
EE	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 500 ppm (1,000 mg/m ³) ② 1,000 ppm (1,900 mg/m ³)
Alberta (CA)	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,880 mg/m ³)
LV	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 mg/m ³
ES from 1 Jan 2013	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	② 1,000 ppm (1,910 mg/m ³) ⑤ s
BC (CA)	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	② 1,000 ppm
VLA (FR)	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,900 mg/m ³) ② 5,000 ppm (9,500 mg/m ³)
SI from 4 Dec 2018	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 500 ppm (960 mg/m ³) ② 1,000 ppm (1,920 mg/m ³) ⑤ Y
TW	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,880 mg/m ³)
WEL (GB)	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,920 mg/m ³)
KR	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,900 mg/m ³)
IS	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,900 mg/m ³)
HU from 7 Feb 2020	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,900 mg/m ³ ② 3,800 mg/m ³ ⑤ N
RU	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 mg/m ³ ③ 2,000 mg/m ³



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
GR from 1 Oct 2016	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,900 mg/m ³)
IDLH (US) from 1 Jan 1994	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 3,300 ppm [10% LEL]
OSHA (US)	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,900 mg/m ³)
NIOSH (US)	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,900 mg/m ³)
ACGIH (US) from 1 Jan 2016	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	② 1,000 ppm
TRGS 900 (DE) from 29 Mar 2019	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 200 ppm (380 mg/m ³) ② 800 ppm (1,520 mg/m ³) ⑤ DFG, Y
Québec (CA) from 1 Apr 2022	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	② 1,000 ppm
CH from 1 Jan 2022	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 ppm (26 mg/m ³) ② 20 ppm (52 mg/m ³) ⑤ (Dampf und Aerosol; kann über die Haut aufgenommen werden) H SSC; Tox: OAW Auge
BE	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ③ 40 ppm (104 mg/m ³) ⑤ (Aérosol, peut être absorbé par la peau) D, M
CZ from 1 Mar 2020	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 19.4 ppm (50 mg/m ³) ② 38.8 ppm (100 mg/m ³) ⑤ (může pronikat pokožkou) D
PL	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 15 mg/m ³ ② 50 mg/m ³ ⑤ (może przenikać przez skórę do organizmu) skóra
NO from 1 Jul 2021	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (damp og Aerosol, kan absorberes gjennom huden) HE5S
TRGS 900 (DE)	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 ppm (26 mg/m ³) ② 20 ppm (52 mg/m ³) ⑤ (Aerosol und Dampf, kann über die Haut aufgenommen werden) DFG, EU, H, Y, 11
IE from 17 Jan 2020	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (may be absorbed through the skin) Sk, IOELV
MY from 1 Jan 2000	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	③ 39.4 ppm (100 mg/m ³)
HTP (FI)	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (50 mg/m ³) ② 40 ppm (100 mg/m ³) ⑤ (voivat imeytyä ihon läpi) iho



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
LT from 15 Oct 2007	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 ppm (25 mg/m ³) ② 20 ppm (50 mg/m ³) ⑤ (garų ir Aerosolis) (tikėtinas įsisavinimas per odą) Šis RD taikomas bendrai garų ir aerosolio koncentracijai. O
SE from 1 Jun 2016	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 ppm (25 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (kan absorberas genom huden)
NPEL (SK) from 23 Nov 2011	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (rátajte so vstrebávaním cez pokožku) K
MAK (AT)	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 ppm (26 mg/m ³) ⑤ (kann über die Haut aufgenommen werden) H
DK	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 mg/m ³ ② 20 mg/m ³ ⑤ (forstøvet)
DK from 28 Jun 2022	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 ppm (26 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (kan optages gennem huden) EH
MAK (AT)	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	② 20 ppm (52 mg/m ³) ⑤ (max. 8x5 min./Schicht, Momentanwert, kann über die Haut aufgenommen werden) H
BG from 6 Jan 2012	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (трябва да се очаква абсорбиране през кожата)
HR	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (mora se uzeti u obzir prodiranje kroz kožu) koža
ES	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (puede ser absorbido a través dérmica) vía dérmica, VLI
RO from 21 Aug 2018	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (e de așteptat asimilarea prin piele) P
EE from 17 Jan 2020	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (naha kaudu kergesti absorbeeruvad ained, aur ja Aerosool) A, 18
LV	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (var absorbet caur adu) Āda
Alberta (CA)	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	③ 100 mg/m ³ ⑤ 3
BC (CA) from 1 Mar 2022	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 mg/m ³ ② 20 mg/m ³ ③ 100 mg/m ³ ⑤ (Aerosol)



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
BC (CA) from 1 Mar 2022	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	③ 50 ppm ⑤ (vapor)
IOELV (EU)	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (may be absorbed through the skin)
VRI (FR)	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (peut être absorbé par la peau)
WEL (GB)	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (vapour, may be absorbed through the skin)
SI	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (računati je treba z možnostjo prodiranja skozi kožo) K, Y, EU1
TW	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 mg/m ³ ⑤ (##)
TW	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	③ 50 ppm (127 mg/m ³) ⑤ (#)
WEL (GB)	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 mg/m ³ ⑤ (may be absorbed through the skin)
KR	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	③ 40 ppm (100 mg/m ³) ⑤ (## #(#) ##)
IS	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 ppm (26 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (efnið getur auðveldlega borist inn í líkamann gegnum húð) H
IS	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 ppm (26 mg/m ³) ⑤ (úðaefni, efnið getur auðveldlega borist inn í líkamann gegnum húð)
CN from 1 Jan 2007	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 mg/m ³ ② 40 mg/m ³
HU	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 52 mg/m ³ ② 104 mg/m ³ ⑤ (felvehető a bőrön keresztül) b, i, N
RU	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 5 mg/m ³ ③ 10 mg/m ³
GR from 1 Oct 2016	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 50 ppm (125 mg/m ³) ② 50 ppm (125 mg/m ³)
NL from 20 Jan 2021	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 52 mg/m ³ ② 104 mg/m ³ ⑤ (damp, kan door de huid in het lichaam worden opgenomen) H
ACGIH (US) from 1 Jan 2017	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	② 10 mg/m ³ ⑤ (inhalable fraction Aerosol)



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
NL	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 mg/m ³ ⑤ (deeltjes)
TR	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (cilt yoluyla alınabilir) Deri
ACGIH (US) from 1 Jan 2017	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	① 25 ppm ② 50 ppm ⑤ (vapor)
Québec (CA)	1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	③ 50 ppm (127 mg/m ³)
CH from 1 Jan 2022	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (590 mg/m ³) ② 200 ppm (590 mg/m ³) ⑤ (kann über die Haut aufgenommen werden) H SSC B; Tox: OAW NS; Messmeth: INRS NIOSH OSHA
MAK (AT)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 100 ppm (295 mg/m ³) ⑤ (kann über die Haut aufgenommen werden) H
BE	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³)
CZ from 1 Mar 2020	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200.4 ppm (600 mg/m ³) ② 300.6 ppm (900 mg/m ³) ⑤ I
PL from 1 Oct 2005	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 450 mg/m ³ ② 900 mg/m ³ ⑤ (może przenikać przez skórę do organizmu) skóra
NO	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 75 ppm (220 mg/m ³) ⑤ E
IE	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³) ⑤ (may be absorbed through the skin) Sk, IOELV
HTP (FI)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	② 100 ppm (300 mg/m ³) ⑤ (voivat imeytyä ihon läpi) iho
LT	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³) ⑤
SE from 1 Jun 2016	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 50 ppm (150 mg/m ³) ② 300 ppm (900 mg/m ³)
NPEL (SK) from 23 Nov 2011	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³)
DK from 28 Jun 2022	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 50 ppm (145 mg/m ³) ② 300 ppm (900 mg/m ³) ⑤ (kan optages gennem huden) EH
MAK (AT)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	② 200 ppm (590 mg/m ³) ⑤ (max. 4x30 min./Schicht, kann über die Haut aufgenommen werden) H



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
BG	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 590 mg/m ³ ② 885 mg/m ³
HR	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³)
ES	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³) ⑤ VLB®, VLI
RO	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³)
EE	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³)
MY from 1 Jan 2000	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (590 mg/m ³)
LV from 1 Feb 2011	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 67 ppm (200 mg/m ³) ② 300 ppm (900 mg/m ³)
Alberta (CA)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (590 mg/m ³) ② 300 ppm (885 mg/m ³)
BC (CA)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 50 ppm ② 100 ppm
IOELV (EU)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³)
VRC (FR)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³) ⑤ (peut être absorbé par la peau)
JP	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (590 mg/m ³)
WEL (GB)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (899 mg/m ³)
SI	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³) ⑤ (računati je treba z možnostjo prodiranja skozi kožo) K, Y, BAT, EU1
TW	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (590 mg/m ³)
KR	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (590 mg/m ³) ② 300 ppm (885 mg/m ³)
IS	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 50 ppm (145 mg/m ³) ② 300 ppm (900 mg/m ³) ⑤ (efnið getur auðveldlega borist inn í líkamann gegnum húð) H
HU	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 600 mg/m ³ ② 900 mg/m ³ ⑤ (felvehető a bőrön keresztül) b, i, N



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
CN from 1 Jan 2007	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 300 mg/m ³ ② 600 mg/m ³
NL from 1 Jan 2023	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 197 ppm (590 mg/m ³) ② 300 ppm (900 mg/m ³) ⑤ (kan door de huid in het lichaam worden opgenomen) H
GR from 1 Oct 2016	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³)
TR	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 300 ppm (900 mg/m ³)
RU from 2 Jan 1900	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 mg/m ³ ③ 400 mg/m ³
IDLH (US) from 1 Jan 1994	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 3,000 ppm
OSHA (US)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (590 mg/m ³)
NIOSH (US)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (590 mg/m ³) ② 300 ppm (885 mg/m ³)
ACGIH (US)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (590 mg/m ³) ② 300 ppm (885 mg/m ³)
Québec (CA)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 50 ppm (150 mg/m ³) ② 100 ppm (300 mg/m ³)
TRGS 900 (DE)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	① 200 ppm (600 mg/m ³) ② 200 ppm (600 mg/m ³) ⑤ (kann über die Haut aufgenommen werden) DFG, EU, H, Y
ACGIH (US)	Citral; 3,7-Dimethyl-2,6-octadienal CAS No.: 5392-40-5 EC No.: 226-394-6	① 5 ppm ⑤ (inhalable fraction and vapor, may be absorbed through the skin)
PL	Citral; 3,7-Dimethyl-2,6-octadienal CAS No.: 5392-40-5 EC No.: 226-394-6	① 27 mg/m ³ ② 54 mg/m ³
IE from 21 Aug 2018	Citral; 3,7-Dimethyl-2,6-octadienal CAS No.: 5392-40-5 EC No.: 226-394-6	① 5 ppm ⑤ (inhalable fraction and vapour)
BE from 21 Jan 2020	Citral; 3,7-Dimethyl-2,6-octadienal CAS No.: 5392-40-5 EC No.: 226-394-6	① 5 ppm (32 mg/m ³) ⑤ (vapeur et Aérosol; peut être absorbé par la peau) D
ES from 1 May 2021	Citral; 3,7-Dimethyl-2,6-octadienal CAS No.: 5392-40-5 EC No.: 226-394-6	① 5 ppm ⑤ (puede ser absorbido a través dérmica, [EinatmFraktK][und][Dampf1]) vía dérmica, Sen, FIV
NO	dipentene CAS No.: 138-86-3 EC No.: 205-341-0	① 25 ppm (140 mg/m ³) ⑤ A



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
LT	dipentene CAS No.: 138-86-3 EC No.: 205-341-0	① 25 ppm (150 mg/m ³) ② 50 ppm (300 mg/m ³) ⑤ Spygliuociu sakai jautrina oda. Atskiru terpenu, išskyrus 3-karena, jautrinantis poveikis nera iširtas. J
SE	dipentene CAS No.: 138-86-3 EC No.: 205-341-0	① 25 ppm (150 mg/m ³) ③ 50 ppm (300 mg/m ³) ⑤ (cf. Terpenes)
EE from 17 Jan 2020	dipentene CAS No.: 138-86-3 EC No.: 205-341-0	① 25 ppm (150 mg/m ³) ② 50 ppm (300 mg/m ³) ⑤ 10
RU	bronopol CAS No.: 52-51-7 EC No.: 200-143-0	③ 3 mg/m ³

8.1.2. Biological limit values

Limit value type (country of origin)	Substance name	Limit value	① Parameter ② Test material ③ Time of sampling: ④ Remark
TRGS 903 (DE) from 9 Nov 2015	butanone CAS No.: 78-93-3 EC No.: 201-159-0	2 mg/L	① 2-Butanon ② Urin ③ Expositionsende bzw. Schichtende
BAT (CH) from 1 Jan 2016	butanone CAS No.: 78-93-3 EC No.: 201-159-0	2 mg/L	① 2-Butanon ② Urin ③ Expositionsende bzw. Schichtende
VLB (ES)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	2 mg/L	① Metiletilcetona ② orina ③ fin de exposición o fin de turno
OEL-B (JP)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	5 mg/L	① Methylethylketone ② # ③ ##### ④ or a few hours
VLBO (RO)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	2 mg/L	① Metiletilcetona ② urina ③ finalul expunerii, resp. finalul schimbului
ACGIH-BEI (US)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	2 mg/L	① MEK ② urine ③ end of exposure or end of shift
BIO (HR)	butanone CAS No.: 78-93-3 EC No.: 201-159-0	2.6 mg/g kreatinin	① etil-metil-ke-ton ② urin ③ kraj izloženosti, odnosno kraj smjene
BAT (SI) from 11 May 2021	butanone CAS No.: 78-93-3 EC No.: 201-159-0	2 mg/L	① metil etil ke-ton ② urin ③ ob koncu delovne izmene
BIO (HU) from 7 Feb 2020	butanone CAS No.: 78-93-3 EC No.: 201-159-0	2 mg/L	① Metil-etil-ke-ton ② vizelet ③ expozíció vége illetve műszak vége



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

Limit value type (country of origin)	Substance name	Limit value	① Parameter ② Test material ③ Time of sampling: ④ Remark
BMGV (GB) from 3 Jan 1900	butanone CAS No.: 78-93-3 EC No.: 201-159-0	70 µmol/L	① butan 2-one ② urine ③ end of exposure or end of shift

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	950 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	114 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	1,900 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	950 mg/m ³	① DNEL Consumer ② Acute - inhalation, local effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	343 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	206 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	35 mg/m ³	① DNEL worker ② Long-term - inhalation, local effects
1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	106 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
butanone CAS No.: 78-93-3 EC No.: 201-159-0	600 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
butanone CAS No.: 78-93-3 EC No.: 201-159-0	106 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
butanone CAS No.: 78-93-3 EC No.: 201-159-0	1,161 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
butanone CAS No.: 78-93-3 EC No.: 201-159-0	412 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
butanone CAS No.: 78-93-3 EC No.: 201-159-0	31 mg/kg bw/ day	① DNEL Consumer ② Long-term - oral, systemic effects
dipentene CAS No.: 138-86-3 EC No.: 205-341-0	33.3 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects

Substance name	PNEC Value	① PNEC type
1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	10 mg/L	① PNEC aquatic, freshwater
1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	1 mg/L	① PNEC aquatic, marine water
1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	37 mg/kg	① PNEC sediment, freshwater

Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

Substance name	PNEC Value	① PNEC type
1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	3.7 mg/kg	① PNEC sediment, marine water
1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	1.53 mg/kg	① PNEC soil
1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	10 mg/L	① PNEC aquatic, intermittent release

* **8.2. Exposure controls****8.2.1. Appropriate engineering controls**

Use only in well-ventilated areas.

Take precautionary measures against static discharges.

8.2.2. Personal protection equipment**Eye/face protection:**Suitable eye protection: Eye glasses with side protection
DIN-/EN-Norms EN 166**Skin protection:**

Hand protection

Suitable material: NBR (Nitrile rubber), PVC (polyvinyl chloride)

Thickness of the glove material: $\geq 0,4$ mm

Breakthrough time: 480 min

Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Tested protective gloves must be worn: EN ISO 374

Suitable protective clothing: Protective clothing

Respiratory protection:

Usually no personal respiratory protection necessary.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Filtering device with filter or ventilator filtering device of type: AX

Thermal hazards:

To avoid thermal decomposition do not overheat.

8.2.3. Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties* **9.1. Information on basic physical and chemical properties****Appearance****Physical state:** Liquid**Colour:** blue**Odour:** Lemon**Safety relevant basis data**

Parameter	Value	at °C	① Method ② Remark
pH	6 - 7	20 °C	
Melting point	<i>not determined</i>		
Freezing point	-60 °C		
Initial boiling point and boiling range	<i>not determined</i>		
Decomposition temperature	<i>not determined</i>		
Flash point	24 °C		
Evaporation rate	<i>not determined</i>		
Auto-ignition temperature	<i>not determined</i>		



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

Parameter	Value	at °C	① Method ② Remark
Upper/lower flammability or explosive limits	<i>not determined</i>		
Vapour pressure	<i>not determined</i>		
Vapour density	<i>not determined</i>		
Density	915 kg/m ³	20 °C	
Relative density	<i>not determined</i>		
Bulk density	<i>not determined</i>		
Water solubility	completely miscible		
Partition coefficient: n-octanol/water	<i>not determined</i>		
Dynamic viscosity	<i>not determined</i>		
Kinematic viscosity	<i>not determined</i>		

* **9.2. Other information**

Not applicable

SECTION 10: Stability and reactivity* **10.1. Reactivity**

Flammable liquid and vapour.

Reference to other sections: SECTION 10: Stability and reactivity,

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Reference to other sections: SECTION 7: Handling and storage

Heating causes rise in pressure with risk of bursting. Recommended storage temperature: 5-25°C

10.5. Incompatible materials

Strong acid, Oxidising agent

10.6. Hazardous decomposition productsDuring heating or in case of fire, toxic gases is possible. Carbon monoxide (CO) Carbon dioxide (CO₂)**SECTION 11: Toxicological information*** **11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

ethanol CAS No.: 64-17-5 EC No.: 200-578-6
LD₅₀ oral: 10,470 mg/kg (Rat)
LD₅₀ dermal: >2,000 mg/kg (Rabbit)
LC₅₀ Acute inhalation toxicity (gas): 20,000 ppmV 4 h (rat)
LC₅₀ Acute inhalation toxicity (vapour): 124 mg/L (Mouse)
1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3
ATE (oral): ≥536 mg/kg
LD₅₀ oral: ≥7,712 mg/kg (Rat)
LD₅₀ dermal: ≥3,500 mg/kg (Mouse)
LC₅₀ Acute inhalation toxicity (vapour): >2.5 mg/L 6 h (Rat)
LC₅₀ Acute inhalation toxicity (dust/mist): ≥2.5 mg/L 6 h (Rat)
butanone CAS No.: 78-93-3 EC No.: 201-159-0
LD₅₀ oral: 3,300 g/m ³ (Rat)
LD₅₀ dermal: 5,000 g/m ³ (Rabbit)
LC₅₀ Acute inhalation toxicity (vapour): 40 mg/L 4 h (Rat) OECD Prüfrichtlinie 436



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

dipentene CAS No.: 138-86-3 EC No.: 205-341-0
LD₅₀ oral: 4,400 mg/kg (Rat)
LD₅₀ dermal: >5,000 mg/kg (Rabbit)
bronopol CAS No.: 52-51-7 EC No.: 200-143-0
LD₅₀ oral: 193 mg/kg (rat)
LD₅₀ dermal: >2,000 mg/kg (rat) OECD Guideline 402 (Acute Dermal Toxicity)
LC₅₀ Acute inhalation toxicity (dust/mist): >0.12 - <1.14 mg/L 4 h (rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional information:

Frequently or prolonged contact with skin may cause dermal irritation.

* **11.2. Information on other hazards****Endocrine disrupting properties:**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Other information:

No information available.

SECTION 12: Ecological information* **12.1. Toxicity**

ethanol CAS No.: 64-17-5 EC No.: 200-578-6
LC₅₀: 11,000 mg/L 4 d (fish)
LC₅₀: 9,280 mg/L 2 d (crustaceans)
LC₅₀: 13,000 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout))
LC₅₀: 5,012 mg/L
EC₅₀: 9,950 mg/L 2 d (crustaceans)
EC₅₀: 275 mg/L 3 d (Algae/water plant, Chlorella vulgaris)
EC₅₀: >10,000 mg/L 2 d (crustaceans, Daphnia magna (Big water flea))
EC₅₀: 275 mg/L 3 d (Algae/water plant, Chlorella vulgaris)
EC₅₀: 12,340 mg/L 2 d (crustaceans, Daphnia magna (Big water flea))
EC₅₀: 275 mg/L 3 d (Selenastrum capricornutum)
NOEC: 12,340 mg/L 21 d



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3
LC₅₀ : ≥72,860 mg/L 4 d (fish)
LC₅₀ : 72,860 mg/L 4 d (Pimephales promelas)
EC₅₀ : ≥100 mg/L 2 d (crustaceans)
EC₅₀ : ≥3,536 - ≤13,000 mg/L 4 d (Algae/water plant)
EC₅₀ : >1,995 mg/L
NOEC : ≥15,380 - ≤32,000 mg/L 12 d (fish)
NOEC : ≥7,500 - ≤15,000 mg/L 21 d (crustaceans)
NOEC : ≥100 mg/L 3 d (Algae/water plant)
butanone CAS No.: 78-93-3 EC No.: 201-159-0
LC₅₀ : 3,220 mg/L 4 d (fish, Pimephales promelas (fathead minnow))
LC₅₀ : 2,993 mg/L 4 d (fish, Pimephales promelas (fettköpfige Elritze)) OECD Prüfrichtlinie 203
EC₅₀ : 5,090 mg/L 2 d (crustaceans)
EC₅₀ : 308 mg/L 2 d (crustaceans, Daphnia magna (Big water flea)) OECD- Prüfrichtlinie 202
NOEC : 1,240 mg/L (Algae/water plant, Pseudokirchneriella subcapitata (Grünalge))
ErC₅₀ : 2,029 mg/L 4 d (Algae/water plant, Pseudokirchneriella subcapitata (Grünalge)) OECD- Prüfrichtlinie 201
dipentene CAS No.: 138-86-3 EC No.: 205-341-0
LC₅₀ : 17.9 mg/L 3 d (fish)
LC₅₀ : 0.702 mg/L
EC₅₀ : 17 mg/L 2 d (crustaceans)
bronopol CAS No.: 52-51-7 EC No.: 200-143-0
LC₅₀ : 11 mg/L 4 d (fish, Lepomis macrochirus) OECD Guideline 203 (Fish, Acute Toxicity Test)
EC₅₀ : 0.026 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)) OECD Guideline 201 (Alga, Growth Inhibition Test)
EC₅₀ : 1.4 mg/L 2 d (crustaceans, Daphnia magna) OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
NOEC : 0.052 mg/L 3 d (Algae/water plant, Skeletonema costatum) OECD Guideline 201 (Alga, Growth Inhibition Test)
NOEC : >20 mg/L 4 d (fish, Lepomis macrochirus) EPA OPP 72-1 (Fish Acute Toxicity Test)
NOEC : 2.61 mg/L 28 d (fish, Oncorhynchus mykiss (previous name: Salmo gairdneri)) OECD Guideline 215 (Fish, Juvenile Growth Test)
NOEC : 0.27 mg/L 21 d (crustaceans, Daphnia magna) OECD Guideline 211 (Daphnia magna Reproduction Test)
LOEC : 0.88 mg/L 21 d (crustaceans, Daphnia magna) OECD Guideline 211 (Daphnia magna Reproduction Test)

Assessment/classification:

Based on available data, the classification criteria are not met.

Additional ecotoxicological information:

Do not allow uncontrolled discharge of product into the environment.

* **12.2. Persistence and degradability**

ethanol CAS No.: 64-17-5 EC No.: 200-578-6
Biodegradation: Yes, rapidly
1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3
Biodegradation: Yes, rapidly
butanone CAS No.: 78-93-3 EC No.: 201-159-0
Biodegradation: Yes, rapidly
dipentene CAS No.: 138-86-3 EC No.: 205-341-0
Biodegradation: —
bronopol CAS No.: 52-51-7 EC No.: 200-143-0
Biodegradation: Poorly biodegradable.

Biodegradation:

The single components are biodegradable.

* **12.3. Bioaccumulative potential**

ethanol CAS No.: 64-17-5 EC No.: 200-578-6
Log K_{ow} : -0.32
Bioconcentration factor (BCF) : 3.2



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3
Log K_{OW} : = -1.36
butanone CAS No.: 78-93-3 EC No.: 201-159-0
Log K_{OW} : 0.29
dipentene CAS No.: 138-86-3 EC No.: 205-341-0
Log K_{OW} : 4.5
bronopol CAS No.: 52-51-7 EC No.: 200-143-0
Log K_{OW} : 0.18
Bioconcentration factor (BCF) : 3.16 Species: other: calculated value

Accumulation / Evaluation:

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

*** 12.5. Results of PBT and vPvB assessment**

ethanol CAS No.: 64-17-5 EC No.: 200-578-6
Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.
1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3
Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.
butanone CAS No.: 78-93-3 EC No.: 201-159-0
Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.
Citral; 3,7-Dimethyl-2,6-octadienal CAS No.: 5392-40-5 EC No.: 226-394-6
Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.
dipentene CAS No.: 138-86-3 EC No.: 205-341-0
Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.
bronopol CAS No.: 52-51-7 EC No.: 200-143-0
Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

*** 12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations*** 13.1. Waste treatment methods**

Dispose of waste according to applicable legislation.

13.1.1. Product/Packaging disposal**Waste codes/waste designations according to EWC/AVV Directive 2008/98/EC (Waste Framework Directive)**

HP 3	Flammable
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Remark:

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

Waste treatment options**Appropriate disposal / Product:**

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:

Non-contaminated packages may be recycled.





13.2. Additional information

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1993	UN 1993	UN 1993	UN 1993
14.2. UN proper shipping name			
FLAMMABLE LIQUID, N.O.S. (Ethanol , 2-Butanone)	FLAMMABLE LIQUID, N.O.S. (Ethanol , 2-Butanone)	FLAMMABLE LIQUID, N.O.S. (Ethanol , 2-Butanone)	FLAMMABLE LIQUID, N.O.S. (Ethanol , 2-Butanone)
14.3. Transport hazard class(es)			
 3	 3	 3	 3
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
No	No	No	No
14.6. Special precautions for user			
Limited quantity (LQ): 5 L Hazard identification number (Kemler No.): 30 Classification code: F1 Tunnel restriction code: (D/E)	Limited quantity (LQ): 5 L Classification code: F1	Limited quantity (LQ): 5 L EmS-No.: F-E, S-E	No data available

14.7. Maritime transport in bulk according to IMO instruments

No transport as bulk according to IBC Code.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. EU legislation****Other regulations (EU):**

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive], Hazard categories:

- P5c Flammable liquids of Categories 2 or 3, not covered by P5a and P5b

Regulation (EC) No. 648/2004 [Detergents regulation]: Contains: Preservative (bronopol), Fragrances and dyes.

Maximum VOC content of the product in a ready to use condition: 435,54 g/L

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 47.6 weight-%

15.1.2. National regulations **[DE] National regulations****Restrictions of occupation**

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Störfallverordnung (12. BlmschV)**for substances contained in the product:**

Hazard categories:

- P5c Flammable liquids of Categories 2 or 3, not covered by P5a and P5b

Betriebssicherheitsverordnung (BetrSichV)

entzündlich

Technische Anleitung zur Reinhaltung der Luft (TA-Luft)**Remark:**

To follow: 5.2.5



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

Water hazard class**WGK:**

1 - slightly hazardous to water

Source:

Self-classification (mixture; calculation rule).

Technische Regeln für Gefahrstoffe

TRGS 500

TRGS 510

TRGS 900

Berufsgenossenschaftliche Vorschriften (DGUV-Vorschriften)

Berufsgenossenschaftliche Informationen (DGUV-Informationen) 868

Berufsgenossenschaftliche Regeln (DGUV-Regeln) 189, 190, 192, 195

15.2. Chemical Safety Assessment

For the following substances of this mixture a chemical safety assessment has been carried out: Ethanol (Ethyl alcohol), ethanediol (Glycol), 2-butanone (ethyl methyl ketone)

* **15.3. Additional information**

Tactile warning according to EN/ISO 11683.

SECTION 16: Other information* **16.1. Indication of changes**

1.1.	Product identifier
1.3.	Details of the supplier of the safety data sheet
1.4.	Emergency telephone number
2.1.	Classification of the substance or mixture
2.2.	Label elements
2.3.	Other hazards
3.2.	Mixtures
4.2.	Most important symptoms and effects, both acute and delayed
5.1.	Extinguishing media
5.2.	Special hazards arising from the substance or mixture
5.3.	Advice for firefighters
6.1.	Personal precautions, protective equipment and emergency procedures
6.2.	Environmental precautions
6.3.	Methods and material for containment and cleaning up
7.1.	Precautions for safe handling
7.2.	Conditions for safe storage, including any incompatibilities
8.1.	Control parameters
8.2.	Exposure controls
9.1.	Information on basic physical and chemical properties
9.2.	Other information
10.1.	Reactivity
11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008
11.2.	Information on other hazards
12.1.	Toxicity
12.2.	Persistence and degradability
12.3.	Bioaccumulative potential
12.5.	Results of PBT and vPvB assessment
12.6.	Endocrine disrupting properties
13.1.	Waste treatment methods
14.1.	UN number or ID number
14.2.	UN proper shipping name
14.5.	Environmental hazards
14.6.	Special precautions for user
15.1.	Safety, health and environmental regulations/legislation specific for the substance or mixture
15.3.	Additional information
16.1.	Indication of changes



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

16.4.	Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]
16.5.	Relevant R-, H- and EUH-phrases (Number and full text)

16.2. Abbreviations and acronyms

See overview table at www.euphrac.eu

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

16.3. Key literature references and sources for data

EC 1907/2006 - REACH Regulation

1272/2008 EC - Regulation on classification, labeling and packaging of substances and mixtures, and amending Directives 67/548/EEC and 1999/45/EC and Regulation (EC) No 1907/2006

Regulation (EC) No 1907/2006 (REACH), Annex II

European Chemicals Agency (ECHA), C & L classification and labeling inventory

European Chemicals Agency (ECHA), ECHA CHEM Registered substances

OECD The Global Portal to Information on Chemical Substances (ChemPortal)

Institute for Occupational Safety and Health of the German Social Accident Insurance (IFA): GESTIS substance database and International limit values for chemical substances

Federal Environment Agency, Section IV 2.4: Documentation and Information Centre substances hazardous to water Rigoletto (catalog substances hazardous to water)

Substance name	Type	source of supply
1,2-Ethanediol CAS No.: 107-21-1 EC No.: 203-473-3	Classification of the substance or mixture	Source: European Chemicals Agency, http://echa.europa.eu/
Citral; 3,7-Dimethyl-2,6-octadienal CAS No.: 5392-40-5 EC No.: 226-394-6	Classification of the substance or mixture	Source: European Chemicals Agency, http://echa.europa.eu/
bronopol CAS No.: 52-51-7 EC No.: 200-143-0	LD ₅₀ oral; LD ₅₀ dermal; LC ₅₀ Acute inhalation toxicity (dust/mist); LC ₅₀ ; EC ₅₀ ; NOEC; LOEC	Source: European Chemicals Agency, http://echa.europa.eu/

* 16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 3</i>)	H226: Flammable liquid and vapour.	On basis of test data.
STOT-repeated exposure (<i>STOT RE 2</i>)	H373: May cause damage to organs through prolonged or repeated exposure.	Calculation method.

* 16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Supplemental hazard information	
EUH066	Repeated exposure may cause skin dryness or cracking.

16.6. Training advice

No data available



Revision date: 21 Sept 2023 Version: 4 Print date: 21 Sept 2023

16.7. Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

* Data changed compared with the previous version.