



RAVENOL DW-1 Fluid

RAVENOL DW-1 Fluid is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

Due to its special formulation the properties of RAVENOL DW-1 Fluid are crucial. We assure an excellent cold stability.

Application Notes

RAVENOL DW-1 Fluid is specially designed for use in the latest automatic transmissions of Honda.

Please note: Follow manufacturer's original equipment number!

Practice and tested in aggregates with filling

Honda 08200-9008, 08200-9009, Honda 08266-99964, 08266-99967, Honda 08266-99901

Characteristic

RAVENOL DW-1 Fluid offers:

- Extremely low pour Point
- Improved viscosity and coefficient of friction behaviour
- A very good protection against consumption
- Excellent thermal stability
- Improved EP-characteristics
- A good foaming behaviour
- Neutral behaviour towards sealing materials
- Reliable protection against corrosion

Characteristics	Unit	Data	Audit
Density at 20°C	kg/m ³	845,0	EN ISO 12185
Colour		red	visual
Pourpoint	°C	-54	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

30.07.2018

Ravensberger Schmierstoffvertrieb GmbH
Postfach 1163
33819 Werther
Tel.: 05203/9719-0
Fax.: 052039719-40 / 41