



RAVENOL MTF-3 SAE 75W

Special Fluid

RAVENOL MTF-3 SAE 75W is a fully synthetic low-viscosity transmission oil for special manual transmissions. RAVENOL MTF-3 SAE 75W is designed based on special selected base oils and specially coordinated additive treatment. This exceeds the needs of today's application requirements.

RAVENOL MTF-3 SAE 75W is outstanding for use under severe mechanical and thermal stress on transmission oils, even with extended oil change intervals.

Application Notes

RAVENOLMTF-3 SAE 75W is a fully synthetic transmission oil for manual transmissions.

Practice and tested in aggregates with filling

JWS2271, BMW MTF LT-3 2300 7533 818, BMW MTF LT-3 83 22 0 396 706, BMW MTF LT-3 83 22 7 533 818, PSA Standard 9730A8, TOYOTA 08885-81001, 08885-81081, FORD WSS-M2C200-D2, FIAT 9.55550-MZ6, Mercedes A001989840309, MB 235.10, Suzuki 99000-22B27-036, VW/AUDI G 060 726 A2, G 052 171 A2, G 052 512 A2, VW G 070 726 A2, VW G009317A2, VW G 055 532 A2, VOLVO 1161839, 1161838, VW G 052 527

Characteristic

RAVENOL MTF-3 SAE 75W offers:

- A high pressure stable lubricating film even at high oil temperatures and under high stress.
- Outstanding shearing stability and excellent thermal stability.
- Excellent viscosity-temperature properties.
- High oxidation stability.
- Excellent wear protection, outstanding EP properties.
- Low foaming properties even at high speeds.
- Good shifting behaviour even in low temperatures, extremely low pour point.
- Extended life.
- A stable lubricating film even at high oil temperatures and under high stress.

RAVENOL special fluid is special development for special units and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data.

Please note: RAVENOL special fluid is exclusively to apply under the original number, as indicated in the product information. Not sure of the correct fluid, you can ask your garage or the car dealer with respect to the original OEM type and number or consult our advisers. It must be specified the VIN code (Vehicle Identification Number) of your vehicle.

Misapplication of RAVENOL special fluid can lead to malfunction of the unit and cause failure.

Ravensberger Schmierstoffvertrieb GmbH does not liable for failures in case of wrong selection of RAVENOL special fluid.

Characteristics	Unit	Data	Audit
Density at 20°C	kg/m ³	844,0	EN ISO 12185
Colour		yellow brown	visual
Brookfield Viscosity	mPa*s	11.000	ASTM D 2983
Pourpoint	°C	-51	DIN ISO 3016
Copper Strip Test		1b	ASTM D130

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

09.01.2019

Ravensberger Schmierstoffvertrieb GmbH
Postfach 1163
33819 Werther
Tel.: 05203/9719-0
Fax.: 052039719-40 / 41