



## RAVENOL Standard Truck SAE 10W

RAVENOL Standard Truck SAE 10W is mineral mono grade motor oil for trucks. All-season oil for all truck diesel engine types. High protection against friction and abrasion, excellent cold start characteristics. Extended oil change intervals according to manufacturer's recommendations.

### Application Notes

RAVENOL Standard Truck SAE 10W is mono grade motor oil for use in truck diesel engines. Also suitable for stationary plants.

### **Specifications**

API CF/SF

### **Practice and tested in aggregates with filling**

MB 227.0, Caterpillar TO-2, Allison C4, MIL-L2104 E, MAN 270, MTU Type 1, Voith Retarder A, Voith DIWA, ZF TE-ML 02C, 03B, 04B, 06A, 07D

### Characteristic

RAVENOL Standard Truck SAE 10W offers:

- Good shear stability
- High oxidation stability
- Excellent viscosity temperature behaviour
- Convincing detergent and dispersant characteristics
- High safety reserves
- Good cold start characteristics
- Best corrosion protection
- Suitable for catalysts

Characteristics	Unit	Data	Audit
Colour		gelbbraun	visual
Density at 20°C	kg/m <sup>3</sup>	862	EN ISO 12185
Viscosity at 40°C	mm <sup>2</sup> /s	36,9	DIN 51 562
Viscosity at 100°C	mm <sup>2</sup> /s	6,4	DIN 51 562
Viscosity index VI		123	ISO 2909
Pourpoint	°C	-36	DIN ISO 3016
Flash point (COC)	°C	232	DIN ISO 2592
TBN	mg KOH/g	12,0	ASTM D2896

All indicated data are approximate values and are subject to the commercial fluctuations.

All information correspond to the best of our knowledge to the actual situation of the cognitions and our development. Subject to alterations. All references made to DIN-norms are only for the description of the goods. There is no guarantee. In case there will be any problems please contact the technical service.

01.03.2019

Ravensberger Schmierstoffvertrieb GmbH  
Postfach 1163  
33819 Werther  
Tel.: 05203/9719-0  
Fax.: 052039719-40 / 41